American Canal Society Canal Index

Crooked Lake Canal	STA	Abandoned - July 4, 1877					ACS
STATE/PROVINCE: New York State:							HAER
COUNTIES: Yates	1	DATES IN USE	CANAL	L E N G T H SLACKWATER	TOTAL	LIFT LOCKS No./ SIZE	
LOCATION (Endpoints of Canal): Dresden, on Seneca Lake to Penn Yan on Keuka Lake	GEMENTS	1833	8		8	27	90x15
TOPOGRAPHIC MAPS:	ENLAR	· 				-	

instruct significance: Construction of the Crooked Lake Canal was authorized Aprill, 1829 and commenced Apr., 1830. The canal was completed Oct. 10, 1833 at a cost of \$333,287. The size of the 27 locks was 90x15. There was one guard lock. Locks originally of wood; rebuilt of cement masonry at heads, and dry walls with timber and plank facings in chambers; when abandoned, locks were: I stone lift lock, I guard lock and 10 lift locks of stone with timber fenders in chambers, and 16 composite lift locks. The size of the canal prism was 42 and 26 x 4 ft.

The Crooked Lake Canal commences at Dresden, on the western shore of Seneca Lake, into which it emties, at a point about thirteen miles above the foot of the lake at Geneva, and extends westerly to the village of Penn Yan and into Keuka Lake from which it takes its waters.

It rises from Dresden to Penn Yan about 277 feet through twenty-eight locks, in a distance of eight miles.

NAMES & ADDRESSES OF GROUPS CONCERNED WITH CANALS PRESERVATION/RESTORATION:

BIBLIOGRAPHICAL SUBMARY:

Whitford, Noble E.-History of the Canal System of the State of New York,

Vol. II, 1905, cpywrt. 1906
Documents of the Assembly of the State of New York, Vol. III, Nos. 15 to 38, 1877.

Annual Report of the Canal Commissioners of the State of New York, 1873

UNPUBLISHED RECORDS, PHOTOS, DRAWINGS (CEHR, HAER, HABS, Local or Regional Historical Societies, Libraries, etc.):

EXISTING OR RECOMMENDED LANDMARK STATUS (CEHR, National Register, etc.):

14571

REPORTER'S NAME & ADDRESS: Gerald Abendschein, 2132 Harris Road, Waterport, N.Y. DATEFeb. 25/8

RETURN TO: CANAL INDEX COMMITTEE, c/o T.K. Woods: 6939 Eastham Circle; Canton, Ohio 14:708